

TIPS FOR USING SEALING TAPE

Elastic sealing profile made of closed-pored PVC foam with butyl coating. Steam-tight, adhesive on all sides, can be compressed very well. Conditionally UV-resistant, weather-resistant and rot-proof.

1) GYSO-Novabutyl	Ø 4.8 mm	21.0 m roll	3940.2100.20
2) GYSO-Novabutyl	Ø 9.5 mm	11.1 m roll	3940.3230.20

Pre-compressed joint sealing tape made of elastic, fine-pored soft PU foam, impregnated with polyacrylate solution (no wax / paraffin). Self-adhesive on one side, impact-resistant up to 600 Pa, sound and heatinsulating, UV and weather resistant. Meets BG1 according to DIN 18542:2009-07.

3) GYSO-Vokoband BG1	15 x 1.5-4 mm	12 m roll	2962.7830.10
4) GYSO-Vokoband BG1	15 x 5-12 mm	6 m roll	2962.8020.10

Elastic PVC foam, density 110 kg/m³, closed pore, self-adhesive with exposed adhesive surface for quick installation. UV-resistant, rot-proof and weatherproof. Air-tight at 90 % compression, waterproof at 60 %. Calculation of the tape width by the user = 2/3 of the thermal insulation thickness.

5) GYSO-Mont-Band	tape width x 10 mm	10 m roll	Blank on request
-------------------	--------------------	-----------	------------------

Elastic PVC foam, density 190 kg/m³, closed pore, self-adhesive with exposed adhesive surface for fast assembly. Well drilled and screwed through. UV-resistant, rot-proof and weatherproof. Air-tight at 90 % compression, waterproof at 70 %.

6) GYSO-sealing tape G-410	15 x 1.5 mm	60 m roll	3140.4321.10
7) GYSO-sealing tape G-410	19 x 3.0 mm	30 m roll	3140.4901.10
8) GYSO-sealing tape G-410	30 x 3.0 mm	30 m roll	3140.6481.10

Elastic PVC foam, closed pore, self-adhesive on one side. As padding and waterproofing underlay of the snow catcher between the trap or corrugated profile.

9) GYSO-Nail seal PVC	40 x 60 mm	500 pieces/roll	3340.7640.20
-----------------------	------------	-----------------	--------------

PVC foam perforated, one-sided adhesive, gray (round foam caps). For sealing penetrations in composite profiles. Thickness 5 mm, external Ø 120 mm, internal Ø 40 mm.

10) GYSO-Stamping PVC	Ø 120 x 5 mm		3075.7870.11
-----------------------	--------------	--	--------------

One-sided adhesive tape with textile carrier and polyethylene coating.

11) Gyso-Cloth tape 515	48 x 0.22 mm	50 m roll	4352.7291.14
-------------------------	--------------	-----------	--------------


Additional vapour-impermeable version for cassettes with sealing tape on the inside in the joint as an additional measure. Adhesive tape on a butyl rubber basis (thickness 0.8 mm) with laminated, polyester-coated aluminium foil. High adhesion, resistant to weather and UV, very pliant, impermeable to water and vapour.

12) GYSO-Tape V-712	50 x 0.8 mm	10 m roll	4618.7290.10 (without illustration)
---------------------	-------------	-----------	-------------------------------------


Observe the separate data sheets from GYSO AG.

This help sheet is merely a recommendation prepared by Montana Building Systems Ltd. in cooperation with GYSO AG.





Trapezoid and corrugated profiles



Wall cassettes



Sandwich elements



Composite profiles

